

11" 5,000 PSI HYDRIL GK SCREWED ANNULAR

BOP SPECIFICATION SHEET



11" 5,000 PSI HYDRIL GK SCREWED HEAD ANNULAR		
DESCRIPTION	DATA	UNITS
MANUFACTURER	HYDRIL	N/A
PRESSURE RATING	5,000	PSI
VERTICAL BORE	11"	INCHES
HEIGHT	47.810	INCHES
APPROXIMATE WEIGHT	8,200	LBS.
OD CLEARANCE	44.25"	INCHES
HYDRAULIC OPERATING PRESSURE	1500	PSI
MAX HYDRAULIC PRESSURE	1500	PSI
NPT PORT SIZE	1"	INCHES
NUMBER OF PORTS	2	N/A
TOP CONNECTION STUDDED	R-54	N/A
BOTTOM CONNECTION FLANGED	R-54	N/A
GALLONS TO CLOSE	9.81	GALLONS
GALLONS TO OPEN	7.98	GALLONS
LIFTING EYE CAPACITY (TOTAL 4)	8,200	LBS TOTAL

Fabritech MS, Inc. is an API 16A licensed facility that manufactures and remanufactures BOP's. The above table is intended for reference to HYDRIL (GE) BOP, and should be further consulted with the OEM of the equipment. It is the user's responsibility to ensure all equipment is in good working order prior to operation. Fabritech MS, Inc. is not responsible for misuse of equipment, or any results that arise from the information on this sheet.

www.Fabritechms.com
Sales@Fabritechms.com