

# 13-5/8" 5,000 PSI HYDRIL GK SCREWED ANNULAR

## BOP SPECIFICATION SHEET



13-5/8" 5,000 PSI HYDRIL GK SCREWED HEAD ANNULAR		
DESCRIPTION	DATA	UNITS
MANUFACTURER	HYDRIL	N/A
PRESSURE RATING	5,000	PSI
VERTICAL BORE	13-5/8"	INCHES
HEIGHT	54.130"	INCHES
APPROXIMATE WEIGHT	13,800	LBS.
OD CLEARANCE	52.250"	INCHES
HYDRAULIC OPERATING PRESSURE	1500	PSI
MAX HYDRAULIC PRESSURE	1500	PSI
NPT PORT SIZE	1"	INCHES
NUMBER OF PORTS	2	N/A
TOP CONNECTION STUDDED	BX-160	N/A
BOTTOM CONNECTION FLANGED	BX-160	N/A
GALLONS TO CLOSE	17.98	GALLONS
GALLONS TO OPEN	14.16	GALLONS
LIFTING EYE CAPACITY (TOTAL 4)	13,800	LBS TOTAL

Fabritech MS, Inc. is an API 16A licensed facility that manufactures and remanufactures BOP's. The above table is intended for reference to HYDRIL (GE) BOP, and should be further consulted with the OEM of the equipment. It is the user's responsibility to ensure all equipment is in good working order prior to operation. Fabritech MS, Inc. is not responsible for misuse of equipment, or any results that arise from the information on this sheet.

[www.Fabritechms.com](http://www.Fabritechms.com)  
[Sales@Fabritechms.com](mailto:Sales@Fabritechms.com)