

# 7-1/16" 10,000 PSI HYDRIL GK SCREWED ANNULAR

## BOP SPECIFICATION SHEET



7-1/16" 10,000 PSI HYDRIL GK SCREWED HEAD ANNULAR		
DESCRIPTION	DATA	UNITS
MANUFACTURER	HYDRIL	N/A
PRESSURE RATING	10,000	PSI
VERTICAL BORE	7-1/16"	INCHES
HEIGHT	48.130	INCHES
APPROXIMATE WEIGHT	12,200	LBS.
OD CLEARANCE	49.50"	INCHES
HYDRAULIC OPERATING PRESSURE	1500	PSI
MAX HYDRAULIC PRESSURE	1500	PSI
NPT PORT SIZE	1"	INCHES
NUMBER OF PORTS	2	N/A
TOP CONNECTION STUDDED	BX-156	N/A
BOTTOM CONNECTION FLANGED	BX-156	N/A
GALLONS TO CLOSE	9.42	GALLONS
GALLONS TO OPEN	7.08	GALLONS
LIFTING EYE CAPACITY (TOTAL 4)	12,200	LBS TOTAL

Fabritech MS, Inc. is an API 16A licensed facility that manufactures and remanufactures BOP's. The above table is intended for reference to HYDRIL (GE) BOP, and should be further consulted with the OEM of the equipment. It is the user's responsibility to ensure all equipment is in good working order prior to operation. Fabritech MS, Inc. is not responsible for misuse of equipment, or any results that arise from the information on this sheet.

[www.Fabritechms.com](http://www.Fabritechms.com)  
[Sales@Fabritechms.com](mailto:Sales@Fabritechms.com)